

Fan inlet airflow sensor

MFS-FI

Mi-269gb / 2009-11-11

Application

Micatrone flow sensor MFS-FI is designed for mounting in the fan air inlet.

Function

MFS-FI is connected through pressure tubes to a Micatrone Flow transmitter which convert the measured pressure to a flow linear output signal.

The location of the installed sensor is carefully tried out to obtain a correct and stable average value of the air flow. Depending on different design of the fan, it may be necessary to adjust the K-factor of the flow sensor, K_m , if the measured value should correspond to withstanding formula.

Flow, Q , is calculated with below standing formula:

$$Q = K_m \times A \times K_{korr} \times \sqrt{\Delta p}$$

$$Q = m^3 / s$$

$$\Delta p = Pa$$

$$K_m = 0,86$$

$$A = \left(\frac{D}{2}\right)^2 \times \pi$$

D = fan inlet diameter in metres closest to the fan wheel.

NOTE! On double suction fans the area (A) is multiplied with 2 ($A \times 2$).

K_{korr} = Correction factor, 0,8...1,2, normally at first calculation, let K_{korr} be 1,0

Adjustment with K_{korr} can be performed in connection with air flow trimming.







Mounting

The flow sensor mounting bracket is fastened on to the fan housing according to figure in such a way that the brackets sensor edge is lined with the smallest diameter of the fan inlet, +/- 10mm.

The sensor can be mounted in any position around the inlet but must be in line with the fan wheel centre.

The flow sensor is in standard delivered with 90° rapid fittings of swivel type for 8/6 plastic tube. Other fittings are available as option.



AB Micatrone
Åldermansvägen 3
SE-171 48 SOLNA
SWEDEN

Phone: +46 8-470 25 00
Fax: +46 8-470 25 99
Internet: www.micatrone.se
E-mail: info@micatrone.se