

GAS DETECTOR GRI-NO2



sensor made in Switzerland



Features

- Three kind of signal output, RS485 and 4~20mA (three wire) digital / analog signal and switch at the same time
- Big screen segment type LCD real-time display gas concentration
- Gas concentration unit optional (such as ppm, mg/m3)
- It can be set high and low alarm point, two level sound and light alarm
- Two relay to control peripheral devices
- Good sealing, anti-corrosion, explosion-proof and anti EMI, RFI function
- Round casting stainless steel housing is suitable for offshore platforms, as well as high temperature, high humidity and other harsh environments

Technical Data

Measuring type : Diffusion
Sensor type : Electro-chemical
Measuring range : 0...1/ 2/ 20/ 100/ 200/ 500/ 1000/ 5000 ppm
Accuracy : ±2 %FS
Resolution : 0.01/ 0.01/ 0.01/ 0.1/ 0.1/ 1/ 1/ 1 ppm
Life expectancy : 1...3 years
Body material : Cast aluminum
Electrical connection : M26 x P2.0
Explosion proof : Exd II CT6
Protection : IP65
Preheating time : 1 min
Alarm error : ±10% of set value
Operating temperature : -10...+40 °C
Operating humidity : 0...85 %RH
Operating pressure : 860...1060 hPa
Power supply : 24 Vdc
Current consumption : 20...200 mA
Power consumption : ≤ 3W
Signal output : 4-20 mA, RS485
Relay : SPST relay 2 channel (0.5 A/125 Vac or 1 A/30 Vdc)
Weight : 1200 g
Dimension : 195 x 178 x 90mm



Ordering code

GRI - NO2 - -
 | |
 A : Alarm
 N : None

1 : Range 0...1 ppm
2 : Range 0...2 ppm
20 : Range 0...20 ppm
100 : Range 0...100 ppm
200 : Range 0...200 ppm
500 : Range 0...500 ppm
1000 : Range 0...1000 ppm
5000 : Range 0...5000 ppm

www.omi.co.th

บริษัท โอเมกา เมชเชอริง อินสตรูเมนต์ จำกัด
 Tel : 02-105-4676
 Fax : 02-903-0080 ext. 6867
 Email : info@omi.co.th
 Line : @omith