

GAS DETECTOR

GIP-CH4



sensor made in Switzerland



Features

- High quality sensor of Membrapor brand from Switzerland
- Big screen LCD real-time display gas concentration
- Sound and light alarm, can be set at high and low point
- 3-color display to indicate the alarm status
- Two relay to control peripheral devices
- Good sealing, anti-corrosion, explosion-proof and anti EMI, RFI function
- Round casting stainless steel housing is suitable for offshore platforms, as well as high temperature, high humidity and other harsh environments

Technical Data

Gas type : Methane (CH₄)
Measuring type : Diffusion
Measuring range : 0...5/ 10/ 20/ 50/ 100 %vol
Accuracy : ±2% of full scale
Resolution : 0.01/ 0.01/ 0.01/ 0.1/ 0.1 %vol
Sensor type : Non-dispersive infrared sensor (NDIR)
Life expectancy : 5...10 years
Preheating time : 60 sec
Operating temperature : -20...+60 °C
Operating humidity : 0...85 %RH
Operating pressure : 700...1300 mbar
Signal output : 4-20 mA (3-wire)
Relay output : 2 x Relay, 0.5A/125Vac or 1A/30Vdc
Power supply : 12...24 Vdc
Current consumption : 20...200 mA
Power consumption : ≤ 3W
Dimension : 195 x 178 x 90mm
Weight : 2.4 kg
Body material : Cast aluminum
Electrical connection : M26 x P2.0
Explosion proof : Ex d IIC T6 Gb
Protection : IP65



Ordering code

GIP - CH4 - -

A : Alarm
N : None

- 5V :** Range 0...5 %vol
- 10V :** Range 0...10 %vol
- 20V :** Range 0...20 %vol
- 50V :** Range 0...50 %vol
- 100V :** Range 0...100 %vol

Example



GIP - (gas type) - (range) - **A**
Gas detector **with alarm**



GIP - (gas type) - (range) - **N**
Gas detector **without alarm**

www.omi.co.th

Omega Measuring Instrument Co., Ltd.
 Tel : 02-105-4676
 Fax : 02-903-0080 ext. 6867
 Email : info@omi.co.th
 Line : @omith