

Weather Station PCE-FWS 20N



Radio weather station to determine the wind direction, wind speed, temperature, relative humidity and rainfall/ Adjustable alarm functions / USB interface / Analysis software / Solar module and batteries for powering the transmitter/ Transmission frequency: 868 MHz

This wireless weather station is a true all-rounder that leaves little to be desired. Whether at home or in the office, the wireless weather station will delight the operator with its versatility. This weather station allows accurate recording of wind direction, wind force, temperature, relative humidity and rainfall. This is just a small selection of the possibilities this weather station offers. In addition, the operator has the possibility to activate various alarm functionson the wireless weather station (wind speed, air pressure, ...). With the help of the values displayed on the weather station, the user can, amongst other things, decide which clothes are appropriate, or whether the garden must be watered, and much more. The weather data is sent up to 100 meters by radio signal to the main station.

The wireless weather station is equipped with the latest technology in weather analysis. The transmitter is powered by a solar panel and the batteries. With the newly developed touch screen display, the weather data can be easily accessed directly from the wireless weather station by simply tapping on the display. With the USB interface and the included USB cable, the weather data can be transmitted directly from the wireless weather station to a PC or laptop. These data are all provided with a time / date stamp in order to be able to assign them even after a longer period of time. Here the weather data can be stored indefinitely. The supplied analysis software then allows you to observe and compare the weather over a longer period of time using graphs and graphics. Everything the user needs for commissioning and use of this wireless weather station is included in the delivery.

- Software for analyzing the stored data
- Backlit 7 inch touch screen
- Weather forecast function
- Automatic time setting thanks to DCF
- Adjustable alarms when the measured value is exceeded
- Wind direction and wind speed
- Temperature and humidity display

Solar panel on the outdoor unit to the supply

Subject to change



Specifications

Inside

Measuring function

Air temperature

Measuring range

0 ... +50 °C 32 ... 122 °F 0.1

Resolution

Accuracy

-

Measuring function

Rel. Humidity		
Measuring range	Resolution	Accuracy
1 99 %	1 %	-

More information



Measuring function

Air Pressure

Measuring function	Resolution	Accuracy
300 1100 hPa	0.1 hPa	± 3 hPa
8.85 32.5 inHg	0.01 inHg	

Measuring interval: 48 seconds Alarm time: 120 seconds

Outside

Measuring function

Air temper	ature
------------	-------

Measuring range	Resolution	Accuracy
-40 60 °C	0.1	±1 °C
-40 140 °F		

Measuring function

Rel. Humidity

Measuring range	Resolution	Accuracy
1 99 %	1 %	±4 % within
		20 80 %
		±6 % within

20 ... 80 %

Rainfall

Measuring range	Resolution	Accuracy
0 9999 mm	0.3 mm at <1000 mm	±6 %
	1 mm at >1000 mm	
Measuring function		
Wind speed		
Measuring range	Resolution	Accuracy
0 50 m/s	0.1	±1 m/s at <5 m/s
0 100 mph		±10 % at >5 m/s

Subject to change



Reception range 100 m, 300 feet Frequency: 868 MHz (Europe) Measuring interval: 48 seconds Protection class: IP X3

Other specifications

7 inch touchscreen

Backlit illuminated display	
Setting the time	manual and automatic (DCF 77)
Power supply display	3 x 1.5 V AA
Power supply outdoor module	2 x 1.5 V AA
Dimensions display	230 x 150 mm
Dimensions outdoor module	400 x 117 mm
Weight display	ca. 551 g
Weight outdoor module	ca. 545 g

Display

- Indoor temperature in Celsius or Fahrenheit
- Outside temperature in Celsius or Fahrenheit
- Indoor humidity
- Outdoor humidity
- Air pressure gauge in inHg or hPa
- Absolute or relative air pressure display selectable
- Precipitation indication in mm or inch
- Rain gauge 1hour, 24 hours, 1 week, 1 month, since the last reset
- Dew point temperature display
- Weather forecast
- Weather forecast trend display
- Storm warning
- Display of weather data
- Programmable alarms for different weather conditions
- Storage of the minimum and maximum values of the received weather data
- Wind speed in mph, km/h, m/s, knots or Beaufort selectable
- Wind direction indicator
- Wind chill temperature display (sensed temperature)
- LED backlight
- Battery life of the weather station about 1 to 2 years
- Radio clock
- 12 or 24 hours display
- Calendar
- Time zone adjustable
- Power savingfunction
- The weather station display can be used as a wall model or stand model
- Permanent adjustment of weather data and radio clock signal
- Ring memory for 4080 complete weather records

(adjustable storage interval 5 to 240 min)

Adjustable alarm functions on the weather station

- Humidity inside max. alarm
- Temperature inside max. alarm

Subject to change



- Humidity outside max. alarm
- Temperature outside max. alarm
- Wind chill max. alarm
- Dew point max. alarm
- Air pressure max. alarm
- Wind speed max. alarm
- Wind gust speed max. alarm
- 1 hour of precipitation max. alarm
- 24 hrs precipitation max. alarm
- Humidity inside min. alarm
- Temperature inside min. alarm
- Humidity outside min. alarm
- Temperature outside min. alarm
- Wind chill min. alarm of the weatherstation
- Dew point min. alarm
- Air pressure min. alarm

Storable measured values via the weather station (with time / date)

- 1 hour of precipitation max.
- 24 hours of precipitation max.
- Week precipitation max.
- Month precipitation max.
- Humidity inside min.
- Temperature inside min.
- Humidity of the weather station outside min.
- Temperature outside min.
- Wind chill temperature min.
- Dew point temperatur min.
- Weather station air pressure min.
- Humidity inside max.
- Temperature inside max.
- Humidity of the weather station outside max.
- Temperature of the weather station outside max.
- Wind chill temperature max.
- Dew point temperature max.
- Air pressure max.
- Wind speed max.
- Wind direction
- Gusts of wind speed max.



