


HUMIDITY AND TEMPERATURE DATA LOGGER HumiStick





Delayed Start		Mission Parameters	Mission Parameters	
D Start Immediately Delay Start By		Sampic Rate 0 🐳 ho		
		Minimum 25.00 -		
0 0 days 0 0 hours 0 0 minutes		Maximum -10.00 ÷		
			Enable Validation Parametera	
D Start On				
12/10/2011 16:47		Absolute Minimum	-30 🚊	
User Parameters		Absolute Moximum	-5 ÷	
		Activation Energy	83 🏯	
Sender	Tecnosoft	Discard from start	0 😤	
Receiver	Megazzino +	Discard from end	0 🔶	
Operator	Andrea -			



www.omi.co.th

Omega Measuring Instrument Co., Ltd. Tel : 02-105-4676 Fax : 02-903-0080 ext. 6867 Email : info@omi.co.th Line : @omith

Features

- Reduced size for easy use for every need
- A special filter protects the sensor from external contaminants and guarantees correct readings.
- Long battery life
- Application for cold chain, environment, pharmaceutical, heathcare, constructions, warehouses, medical, food and beverages, logistic and transport

Technical data

Humidity range: 5...95 %RH Humidity resolution: 0.1 %RH Humidity accuracy : ±3% RH within 20...80% RH, otherwise ±4% RH Temperature range : -30...+60°C Temperature resolution : 0.1°C **Temperature accuracy :** ±0.4°C within +5...+40°C, otherwise ±1°C Memory capacity: 1,365 reading **Battery type :** 3.0V CR2032 lithium (user replaceable) **Battery life** : up to 10 years or 3 millions of acquisitons (*The battery* could run out quickly because the operating temperature) Interval: 1min...255mins Operate system : Windows 7, 8, 10 **Exporting :** Excel Dimension: 50 X 24 X 15 mm (WxHxD) Weight: 11 a Protection: IP50

Accesories (option)



Model : TS04IUSB **Description :** USB interface for connecting with PC



Scan! for video clip Endurance test of the new TempStick, Super resistant, user replaceable battery and splash proof.

