

## GAS DETECTOR GAP-CH20



Sensor made in Switzerland



### Features

- High quality sensor of Membrapor brand from Switzerland
- Built-in pump for suction gas in the measurement
- Full-color 3.5-inch TFT screen, color LCD display
- Intelligent Probe design that convenient calibration and-maintenance
- Digital and graph display of gas concentration.
- High-capacity lithium battery-powered, rechargeable
- Low alarm, High alarm, TWA, STEL with Sound alarm

### Technical Data

**Gas type :** Formaldehyde (CH<sub>2</sub>O)  
**Measuring range :** 0...10/ 50/ 500/ 1000/ 2000 ppm  
**Accuracy :** ±5 % of full scale  
**Resolution :** 0.01/ 0.1/ 1/ 1/ 1 ppm  
**Measuring type :** Pump  
**Sensor type :** Electrochemical  
**Sensor life :** 1...3 years  
**Preheating time :** 60 sec  
**Operating temperature :** -20...+55 °C  
**Operating humidity :** 15...95 %RH, non-condensing  
**Operating pressure :** Atmospheric pressure  
**Power supply :** Lithium battery 4.2V/ 3000 mAh  
**Continuous work hours :** 8...12 hours  
**Charge time :** 6...8 hours  
**Body material :** Polycarbonate  
**Dimension :** 228 x 84 x 50.5 mm  
**Weight :** 550 g  
**Explosion protection :** Ex ib IIB T4 Gb  
**Protection :** IP65

### Ordering code

GAP-CH20-

**10 :** Range 0...10 ppm  
**50 :** Range 0...50 ppm  
**500 :** Range 0...500 ppm  
**1000 :** Range 0...1000 ppm  
**2000 :** Range 0...2000 ppm

[www.omi.co.th](http://www.omi.co.th)

**Omega Measuring Instrument Co., Ltd.**

Tel : 02-105-4676

Fax : 02-903-0080 ext. 6867

Email : [info@omi.co.th](mailto:info@omi.co.th)

Line : @omith