

GAS DETECTOR

GIP-P-Cl2



sensor made in Switzerland



Features

- High quality sensor of Membrapor brand from Switzerland
- Big screen LCD real-time display gas concentration
- Sound and light alarm, can be set at high and low point
- 3-color display to indicate the alarm status
- Two relay to control peripheral devices
- Good sealing, anti-corrosion, explosion-proof and anti EMI, RFI function
- Round casting stainless steel housing is suitable for offshore platforms, as well as high temperature, high humidity and other harsh environments

Technical Data



Gas type : Chlorine (Cl₂)
Measuring type : Pipeline
Measuring range : 0...20/ 200/ 2000/ 5000 ppm
Accuracy : ±2% of full scale
Resolution : 0.01/ 0.1/ 1/ 1 ppm
Sensor type : Electrochemical
Life expectancy : 1...3 years
Preheating time : 60 seconds
Operating temperature (body) : -20...+60 °C
Operating temperature (sensor) : 0...+50 °C
Operating humidity : 0...85 %RH
Operating pressure : -0.3...+0.3 barG
Operating Gas flow rate : 0.4 - 0.8 l/min (Recommend 0.5 l/min)
Signal output : 4-20 mA (3-wire)
Relay output : 2 x Relay, 0.5A/125Vac or 1A/30Vdc
Power supply : 12...24 Vdc
Current consumption : 20...200 mA
Power consumption : ≤ 3W
Pipe connection : connection for tube I.D 4 mm
Dimension : 195 x 178 x 90mm
Weight : 2.4 kg
Body material : Cast aluminum
Electrical connection : M26 x P2.0
Explosion proof : Ex d IIC T6 Gb
Protection : IP65

Ordering code

GIP - P - Cl2 - -

A : Alarm
N : None

20 : Range 0...20 ppm
200 : Range 0...200 ppm
2000 : Range 0...2000 ppm
5000 : Range 0...5000 ppm

www.omi.co.th

Omega Measuring Instrument Co., Ltd.

Tel : 02-105-4676
 Fax : 02-903-0080 ext. 6867
 Email : info@omi.co.th
 Line : @omith

Example



GIP - P -(gas type) - (range) - **A**
Gas detector **with alarm**



GIP - P -(gas type) - (range) - **N**
Gas detector **without alarm**