

GAS DETECTOR

WASP-D1-E-H2O2



Features

- TFT color display
- Fast response, high precision and high stability
- USB rechargeable lithium battery
- Built-in data storage
- Modular structure easy maintenance
- With sound and light alarm, vibration alarm
- Smart sensor platform
- PPM and mg/m³ conversion
- Waterproof and dustproof anti-drop robust housing

Technical Data

Measuring type : Diffusion
Sensor type : Electro-chemical
Measuring range : 0...100, 500, 2000 ppm
Accuracy : ±5 %FS
Resolution : 0.01 ppm
Sensor life : 1 year
Body material : PC+TPE
Preheating time : 1 min
Alarm : sounds, LED light, vibration
Data storage : more than 300,000 value
Operating temperature : -20...+55 °C
Operating humidity : 15...95 %RH, non-condensing
Operating pressure : Atmospheric pressure
Storage temperature : -20...+60 °C
Storage humidity : ≤ 90%RH
Power supply : Lithium battery 3.7V/ 2000 mAh
Continuous work hours : 8 hours
Charge time : < 4 hours
Protection : IP65
Dimension : 110 x 68 x 38 mm
Weight : 200 g

Ordering code

WASP-D1-E-H2O2-

100 : Range 0...100 ppm
500 : Range 0...500 ppm
2000 : Range 0...2000 ppm

www.omi.co.th

บริษัท โอเมก้า เมชเชอริ่ง อินสตรูเมนต์ จำกัด
 Tel : 02-105-4676
 Fax : 02-903-0080 ext. 6867
 Email : info@omi.co.th
 Line : @omith