

## GAS DETECTOR GRI-H2-P



sensor made in Switzerland



### Features

- Three kind of signal output, RS485 and 4~20mA (three wire) digital / analog signal and switch at the same time
- Big screen segment type LCD real-time display gas concentration
- Gas concentration unit optional (such as ppm, mg/m3)
- It can be set high and low alarm point, two level sound and light alarm
- Two relay to control peripheral devices
- Good sealing, anti-corrosion, explosion-proof and anti EMI, RFI function
- Round casting stainless steel housing is suitable for offshore platforms, as well as high temperature, high humidity and other harsh environments



### Technical Data

**Measuring type :** Pipeline (Pump)  
**Sensor type :** Electro-chemical  
**Measuring range :** 0...1000/ 2000/ 5000/ 10000/ 40000 ppm  
**Accuracy :** ±2 %FS  
**Resolution :** 1/ 1/ 1/ 1/ 1 ppm  
**Life expectancy :** 1...3 years  
**Body material :** Cast aluminum  
**Electrical connection :** M26 x P2.0  
**Explosion proof :** Exd II CT6  
**Protection :** IP65  
**Preheating time :** 1 min  
**Alarm error :** ±10% of set value  
**Operating temperature :** -10...+40 °C  
**Operating humidity :** 0...85 %RH  
**Operating pressure :** 860...1060 hPa  
**Power supply :** 24 Vdc  
**Current consumption :** 20...200 mA  
**Power consumption :** ≤ 3W  
**Signal output :** 4-20 mA, RS485  
**Relay :** SPST relay 2 channel (0.5 A/125 Vac or 1 A/30 Vdc)  
**Weight :** 1200 g  
**Dimension :** 195 x 178 x 90mm

### Ordering code

GRI - H2 - P -  -

|

A : Alarm

N : None

**1000 :** Range 0...1000 ppm  
**2000 :** Range 0...2000 ppm  
**5000 :** Range 0...5000 ppm  
**10000 :** Range 0...10000 ppm  
**40000 :** Range 0...40000 ppm  
 : Special request

### www.omi.co.th

บริษัท โอเมก้า เมชเชอริง อินสตรูเมนต์ จำกัด  
 Tel : 02-105-4676  
 Fax : 02-903-0080 ext. 6867  
 Email : info@omi.co.th  
 Line : @omith