

## GAS DETECTOR GNP-P-CIO2



sensor made in Switzerland



### Features

- High quality sensor of Membrapor brand from Switzerland
- Good sealing, anti-corrosion, explosion-proof and anti EMI, RFI function
- Round casting stainless steel housing is suitable for offshore platforms, as well as high temperature, high humidity and other harsh environments

### Technical Data

**Gas type :** Chlorine Dioxide (ClO<sub>2</sub>)

**Measuring type :** Pipeline

**Measuring range :** 0...20/ 200/ 5000 ppm

**Accuracy :** ±2% of full scale

**Resolution :** 0.01/ 1/ 1 ppm

**Sensor type :** Electrochemical

**Life expectancy :** 1...3 years

**Preheating time :** 60 seconds

**Operating temperature (body) :** -20...+60 °C

**Operating temperature (sensor) :** 0...+50 °C

**Operating humidity :** 0...85 %RH

**Operating pressure :** -0.3...+0.3 barG

**Operating Gas flow rate :** 0.4 - 0.8 l/min (Recommend 0.5 l/min)

**Signal output :** 4-20 mA (2-wire)

**Power supply :** 12...24 Vdc

**Current consumption :** 20...200 mA

**Power consumption :** ≤ 3W

**Pipe connection :** connection for tube I.D 4 mm

**Dimension :** 195 x 178 x 90mm

**Weight :** 1.65 kg

**Body material :** Cast aluminum

**Electrical connection :** M26 x P2.0

**Explosion proof :** Ex d IIC T6 Gb

**Protection :** IP65

### Ordering code

GNP - P - ClO<sub>2</sub> -

20 : Range 0...20 ppm

200 : Range 0...200 ppm

5000 : Range 0...5000 ppm

[www.omi.co.th](http://www.omi.co.th)

Omega Measuring Instrument Co., Ltd.

Tel : 02-105-4676

Fax : 02-903-0080 ext. 6867

Email : [info@omi.co.th](mailto:info@omi.co.th)

Line : @omith

