

PURELY OXYGEN GAS DETECTOR

GIP-P-02



sensor made in Switzerland



Features

- High quality sensor of Membrapor brand from Switzerland
- Big screen LCD real-time display gas concentration
- Sound and light alarm, can be set at high and low point
- 3-color display to indicate the alarm status
- Two relay to control peripheral devices
- Good sealing, anti-corrosion, explosion-proof and anti EMI, RFI function
- Round casting stainless steel housing is suitable for off-shore platforms, as well as high temperature, high humidity and other harsh environments

Technical Data

Gas type : Oxygen (O₂)
Measuring type : Pipeline
Measuring range : 0...100 %vol
Accuracy : ±2 %FS
Resolution : 0.1 %vol
Sensor type : Electrochemical
Life expectancy : 2...4 years
Pre-Heating time : 60 sec
Operating temperature (body) : -20...+60 °C
Operating temperature (sensor) : 0...+50 °C
Operating humidity : 0...85 %RH
Operating pressure : 700...1300 mbar
Operating Gas flow rate : 0.4 - 0.8 l/min (Recommend 0.5 l/min)
Signal output : 4-20 mA
Relay output : 2 x Relay, 0.5A/125Vac or 1A/30Vdc
Power supply : 12...24 Vdc
Current consumption : 20...200 mA
Power consumption : ≤ 3W
Pipe connection : connection for tube I.D 4 mm
Body dimension : 195 x 178 x 90mm (H x L x D)
Weight : 2.4 kg
Body material : Cast aluminum
Electrical connection : M26 x P2.0
Explosion proof : Ex d IIC T6 Gb
Protection : IP65

Ordering code

GIP - P - 02 - 100V -

|
 A : Alarm
 N : None

www.omi.co.th

Omega Measuring Instrument Co., Ltd.

Tel : 02-105-4676

Fax : 02-903-0080 ext. 6867

Email : info@omi.co.th

Line : @omith

• Example



GIP-P-(gas type)-(range)-N
Gas detector **without alarm**



GIP-P-(gas type)-(range)-A
O2 gas detector **with alarm**